

Flink
SNOW PLOWS & SPREADERS

HYDRUALIC RF8 ROLL SPREADER RFH8



Under Tailgate Roll
Spreader for:
**Summer Maintenance
and
Winter Ice Control**

The Flink Roll Spreader will handle a variety of granular materials, with the ability to unload over the tailgate without removing the spreader. Captive, hinged end covers on end plates provide easy access to chain drive and gate adjust mechanism. The spreader mounts on the rear of the dump body with "Quick Detach" mounting hardware.

FEATURING

- ◆ Adjustable Manual Gate
or
- ◆ Adjustable Hydraulic Gate
- ◆ Spring Loaded Anit-Flow Plate (Four Section)



- ◆ Full 8' Width Spread
- ◆ Operates in Forward or Reverse

Manufactured by Flink Company
502 N. Vermillion St.
Streator, IL 61364
Phone: (815)673-4321

www.flinkco.com



THROUGH: Welded 7 gauge construction
 One piece hinged & removable heavy duty cover
 Lock handles captive to eliminate loss

FEED MECHANISM:
 Roll is full 96" width, with 1/4" wall thickness
 Roll is 4 1/2" outside diameter
 1 1/4" roll shafts run in three (3) bolt flange bearings
 Bearings heavy duty, sealed, re-lubable and self aligning
 Welded beads on outer diameter of roll
 End plates are slotted for drop out removal of roll
 Four (4) independent spring loaded anti-flow gates
 Gates prevent flow thru in off position
 Rear wear plate is adjustable & replaceable
 Front wear plate is adjustable & replaceable

DRIVE ASSEMBLY:
 Low speed high torque Char-Lynn motor, mounted on adjustable bracket
 Drive chain #60 roller chain
 Chain enclosed by hinged covers
 Covers and latches attached to prevent loss
 Requires 15 GPM at maximum operating speed

FINISH COAT:
 Flink Yellow Standard. Other colors optional

HARDWARE: Tailgate shields, "QUICK DETACH" brackets and lift slots for mounting

OPTIONS: Hydraulic Roll Gate; opens feed gate to present rate
 Valve; single flow control valve with built in relief and manual on/off, cab mounted with 11 positions for flow rate

DIMENSIONS

Model	Overall Length	Roll Length	Width	Height
RF 8	104"	96"	16 3/4"	18"
RFH 8	104"	96"	16 3/4"	18"