



# BAKER 550

# BAKER 550 REVERSIBLE PLOW

FLINK'S BAKER 550 REVERSIBLE SNOW PLOW



## Flared Moldboard Ends

- Increase discharge of snow from curb
- Helps prevent over-riding of snow



## Sectional Trip Edge Design

- Multiple Independent Sections Trip when encountering unforeseen road obstructions.
- Two Dual Spring, Reverse Wound Compression Spring Assemblies per trip section
- Adjustable Tension Trip per section
- Adjustable for proper cutting edge attack angle to road surface

## BAKER PLOW- SPECIFICATIONS

MODEL NUMBER	PLOW HEIGHT	MOLDBOARD THICKNESS	MOLDBOARD LENGTH		SECTIONAL CUTTING EDGES		NO. OF VERTICAL RIBS	PATH CLEARED		APPROX SHIP WEIGHT
			AT BOTTOM	AT TOP	5/8" X 6" X 2' LONG	5/8" X 6" X 3' LONG		AT 28"	AT 35"	
2PR559S	36"	3/16"	10'0"	10'10"	2	2	8	8'10"	8'2"	1450
2PR559U	42"	3/16"	10'0"	10'10"	2	2	8	8'10"	8'2"	1475
2PR554U	42"	3/16"	11'0"	12'0"	4	1	8	9'8"	9'0"	1860



### FEATURES

- 1 Rugged 3/16" plate paneled steel moldboard with 1/4" gussets and main deck; all welding construction. Flared at the top to increase discharge efficiency.
- 2 3" x 2-1/2" x 3/8" angle for top edge reinforcement.
- 3 3-1/2" x 3-1/2" x 1/2" mod-moldboard reinforcement and spring assembly support.
- 4 Heavy-duty, multi-position "A" frame allows reversing to desired angle.
- 5 Two double-acting power reverse cylinders.
- 6 Blade hinge weldments permit 3-14" wear from the 6" cutting edge. Standardized in 2' and 3' lengths on reversibles.
- 7 swivel bar allows to plow to follow contour of road.

### OPTIONS

- Caster Wheels
- Wear Runners
- Pneumatic Tired-Wheels
- Quick Link Swivel Bar
- Tapered Rubber Deflectors
- Manual Angle
- Cutting Edge Shoes
- Jack Stand
- Universal Curb Guards
- One-Piece Cutting Edge
- Cushion Valve



FLINK PRODUCT  
MANUFACTURED BY:



**AUTHORIZED DEALER:**

[www.flinkplows.com](http://www.flinkplows.com) • (800) 851-9664 • [info@bonnell.com](mailto:info@bonnell.com) • 1385 Franklin Grove Rd. • Dixon, IL 61021