



LMC5H

FV-SERIES
Pintle Chain Conveyor



FEATURES & BENEFITS :

- 1 10 - gauge hopper sides ('CS' Carbon 7 - gauge longills
- 2 12 - gauge hopper sides ('SS' Stainless) 10 - gauge longills
- 3 Top screens
- 4 50:1 gear box, 1.5" drive-shaft and 8 tooth sprockets are providing for a longer drag chain life.
- 5 Swing-up spinner with 18" steel spinner disc
- 6 Feed gate



LMC5H HOPPER SPREADER
FLINK'S FV-SERIES V-BOX SPREADER

CARBON STEEL BODY

Constructed of 10-gauge steel with 45° sloping sides with 10-gauge side supports and 7-gauge longills. Each unit comes complete with a 12" x 18" steel feedgate, which is adjustable by means of a screw type jack that is self locking, and is assembled with all stainless steel internal parts.

STAINLESS STEEL BODY

Constructed of 12-gauge steel with 45° sloping sides with 12-gauge side supports and 10 gauge longills. Heavier gauges available.

CONVEYOR

The 24" wide conveyor chain is made of heat-treated, self-cleaning pintle chain with cross bars welded every 4-1/2". The conveyor gearbox is a 50:1 reduction and is a bronze worm-gear type having a cast

iron housing with a ring-mounted bolt pattern. Drive and idler shafts are 1-1/2" with 8 tooth drop forged sprockets, and are mounted in sealed anti-friction bearings. Two spring-loaded adjustment screws, with a minimum of 4" of travel to maintain proper conveyor tension are standard.

SPINNER ASSEMBLY

Swing up assembly with 18" steel spinner disc, four external baffles

TOP SCREENS

Section top screens are made of 3/8" diameter rods welded to a 1/4" x 2" angle iron frame creating a maximum opening of 2-1/2."

OPTIONS:



- Light Bar
- Winch for Swing Up Spinner
- Liquid System



- Electric Tarp
- Chain Oiler
- Catwalk Fenders with Liquid System



- Spill Shields
- Chain Oiler
- Grease Extensions
- Winch For Swing Up Spinner

FV-SERIES SPREADER SPECIFICATIONS

MODEL NUMBER	V-BOX LENGTH	V-BOX HEIGHT	CAB TO AXLE	CUBIC YARD CAPACITY	APPROX. WEIGHT
FV-1050	10'	50"	84"	5.5	2,385 LBS
FV-1056	10'	56"	84"	6.7	2,480 LBS
FV-1062	10'	62"	84"	7.9	2,575 LBS
FV-1150	11'	50"	96"	6.1	2,525 LBS
FV-1156	11'	56"	96"	7.4	2,625 LBS
FV-1162	11'	62"	96"	8.7	2,725 LBS
FV-1250	12'	50"	108"	6.6	2,695 LBS
FV-1256	12'	56"	108"	8.1	2,800 LBS
FV-1262	12'	62"	108"	9.5	2,905 LBS
FV-1350	13'	50"	96" C.T.	7.0	2,835 LBS
FV-1356	13'	56"	96" C.T.	8.6	2,945 LBS
FV-1362	13'	62"	96" C.T.	10.4	3,055 LBS
FV-1450	14'	50"	108" C.T.	7.8	3,005 LBS
FV-1456	14'	56"	108 C.T.	9.5	3,120 LBS
FV-1462	14'	62"	108" C.T.	11.2	3,235 LBS
FV-1550	15'	50"	120" C.T.	8.3	3,145 LBS
FV-1556	15'	56"	120" C.T.	10.2	3,265 LBS
FV-1562	15'	62"	120" C.T.	12.0	3,385 LBS

Longer lengths available upon request

OPTIONS NOT SHOWN:

- Belt over conveyor chain
- Doghouse cutout for dump body hoist



FLINK PRODUCT
MANUFACTURED BY:



AUTHORIZED DEALER: